



JVC GR-D93U Eye Piece Replacement

This guide will show how to take out the eye piece.

Written By: Lindsay



INTRODUCTION

The JVC GR-D93U has both an LCD screen and an eye piece that you can use to see what you are recording.



TOOLS:


- [Phillips #0 Screwdriver](#) (1)
 - [Tweezers](#) (1)
 - [Spudger](#) (1)
-

Step 1 — Eye Piece



- Unscrew two 3mm Phillips #0 screw from the bottom of the camera to remove blue plastic casing.

Step 2




- Unscrew two 3mm Phillips #0 screws. Then remove 6 3mm Philips #0 screws from the bottom of the camera.

Step 3




- Unscrew 3mm Phillips #0 screws from the batter port under the eye piece.

Step 4




- Now the camera can be split into two pieces. Be careful when removing the two sides and remove the cables connecting the two halves. There are also cables that need to be disconnected from the battery pack section.

Step 5



- Unscrew two 3mm Phillips #0 screws from around the eye piece. Then flip the camera over and unscrew 3mm Phillips #0 screw. Then unscrew 3mm Phillips #0 screw from under the eye piece.

Step 6



- Unscrew 3mm Phillips #0 screw and disconnect cable. This will disconnect the eye piece from the camera.

To reassemble your device, follow these instructions in reverse order.

This document was last generated on 2017-06-22 05:05:54 PM.